

Specification	SG-230	SG-235	SG-237	SG-239	MAC-200
Frequency Range	1.6 - 30MHz	1.8 - 30MHz	1.8 - 60MHz	1.8 - 30MHz	1.8 - 60MHz
Input Power Range (PEP)	3 - 200W	3 - 500W	3 - 100W	1.5 - 200W	1.5 - 200W
Input Power Max. (CW)	80W	200W	40W	80W	80W
Input Impedance Range	45 - 55 ohms	45 - 55 ohms	45 - 55 ohms	45 - 55 ohms	45 - 55 ohms
Typical VSWR	< 2:1	< 2:1	< 2:1	< 2:1	< 2:1
DC Input Requirement	+ 13.6 VDC	+ 13.6 VDC	+ 13.6 VDC	+ 13.8 VDC	+ 13.8 VDC
DC Operating Range	10 - 18 VDC	10 - 18 VDC	10 - 18 VDC	10 - 18.5 VDC	10 - 18.5 VDC
Input Current (Average)	.9 Amps	1.4 Amps	.3 Amps	.23 Amps	.23 Amps
Initial Tune Time	< 2 seconds	< 2 seconds	< 4 seconds	< 2 seconds	< 2 seconds
From Memory Tune Time	< 10 ms	< 10 ms	< 10 ms	< 10 ms	< 10 ms
Memory Bins	170	170	170	170	170
Tuning Combinations	1/2 million	1/2 million	1/2 million	1/8 million	1/8 million
Antenna Length (> 3.3MHz)	8 feet	50 feet	8 feet	40 feet	40 feet
Antenna Length (< 3.3MHz)	23 feet	300 feet	28 feet	100 feet	100 feet
Elements Configuration	Pi & L	Pi & L	Pi & L	Pi & L	Pi & L
Input Capacitance (Min.)	100 pF	100 pF	50 pF	50 pF	50 pF
Input Capacitance (Max.)	6400 pF	6400 pF	6400 pF	3150 pF	3150 pF
Inductance (Min.)	0.25 µH	0.125 µH	0.125 µH	0.125 µH	.125 µH
Inductance (Max.)	64 µH	32 µH	32 µH	16 µH	16 µH
Output Capacitance (Min.)	25 pF	12.5 pF	12.5 pF	50 pF	50 pF
Output Capacitance (Max.)	800 pF	400 pF	200 pF	740 pF	740 pF
Installation	Any Position ²	Any Position ²	Any Position ²	Any Position ²	Desktop ²
Operating Temperature	-35C to +70C	-35C to +70C	-35C to +70C	-35C to +70C	-35C to +70C
Environmental	Waterproof under 2 ft. for 30 min.	Waterproof under 2 ft. for 30 min.	Waterproof under 2 ft. for 30 min.	No protection	No protection
Dimensions (L x W x H Inches)	16 x 12 x 3	16 x 12 x 3	6 x 7 x 1.5	7.5 x 6 x 2	8.5 x 6.5 x 3
Weight (Lbs.)	8 lbs.	8 lbs.	< 2 lbs.	2 lbs.	5 lbs.
Case Construction	Sealed ABS Plastic	Sealed ABS Plastic	Sealed ABS Plastic	Aluminum ³	Extruded Metal ³
Control Cable *	9 ft. coax/control	9 ft. coax/control	9 ft. coax/control	not supplied	not supplied
Other				Wire Terminals Manual Tune	5 Outputs ¹ 2 Meters ¹

¹ See specifications on specific for details.

² Ideal installation position for all SGC couplers is as close to antenna feed point as possible.

³ Not recommended for outside installation - requires additional protection.

* All SGC couplers require only RF and DC power(not required for SG-211). SGC cables are required for additional features only.